

#### Industrial / Spectacles / 506 UP 506 UP - In/Out G65 Code: 506U.63.08.00

#### Date: 17-05-24 1/2

506 UP presents technical and aesthetic improvements. The panoramic and wrapping lens is available with Vanguard Plus coating for superior performance in all conditions. The temples with rubber tips and adjustable in length and inclination, the total adaptability of the nosepad and the new range of vibrant colors allow a high degree of customisation of the device.



Frame mark (EU)	Lens mark (EU)	Frame technology
506U U 166 FT CE	2C-1.4/5-1.4 U 1 FT K N CE	Nose pad set-up, Adjustment of temples in length, Adjustment of temples in inclination, Rubber Terminal
Conditions of use	Lens technology	Lens color
Standard brightness, Low brightness, Indoor - Outdoor	Anti-Scratch + Anti-Fog (KN - Vanguard PLUS), In/Out G65	Clear
Lens material	Frame color	Standards
Polycarbonate	Black/Green	EN166, EN170, EN172
Scale number	Mechanical resistance	Optional requirements
(2C-1.4), (5-1.4)	Low energy impact (F)	Resistance to surface damage by fine particles (K), Resistance to fogging of oculars (N), Protection against high speed particles at extreme temperatures -5°/+55° C (T)
Optical class	Weight	
Optical class (1)	25g	

#### Industrial / Spectacles / 506 UP

2/2

>> https://www.univetsafety.com/en/products/safety/spectacles/506-up/506-up-in-out-g65/



## 01.

TEMPLES ADJUSTABLE IN LENGTH AND INCLINATION

## 02.

OPTIMAL COMFORT AND FIT THANKS TO THE SOFT ADJUSTABLE NOSE PAD

# 03.

PANORAMIC AND WRAPAROUND LENS FOR A BETTER SIDE PROTECTION

### 04.

SOFT TERMINAL TIPS TO ELIMINATE LOCAL PRESSURE

Attention! Any images on this page illustrate the frame technologies of the product family in question and may represent frame and lens colours that do not correspond to the product code of the following sheet.

#### HEADQUARTERS